## ANTI-COLLISION SYSTEM FOR VEHICLES

Also published as: Publication number: JP9505781 (T) Publication date: 1997-06-10 WO9324894 (A1) Inventor(s): US5357438 (A) Applicant(s): IL102097 (A) Classifications P EP0643854 (A1) - international: B60R21/00; B60K37/06; B60Q1/52; B60W30/00; F02D29/02; P0643854 (A4) G01S13/93; G08G1/16; G01S7/04; G01S13/60; B60R21/00; B60K37/04; B60Q1/50; B60W30/00; F02D29/02; G01S13/00; G08G1/16; G01S7/04; (IPC1-7): B60R21/00; F02D29/02: G08G1/16


- European: B60K37/06; B60Q1/52A; G01S13/93C

Application number: JP19930500886T 19930604

Priority number(s): IL19920102097 19920604; WO1993US05425 19930604

Abstract not available for JP 9505781 (T) Abstract of corresponding document: WO 9324894 (A1)

An anti-collision system for vehicles includes a speed sensor (12) for sensing the speed of the vehicle (2), a space sensor (8) for measuring the distance of the vehicle (2) from an object, a computer (4) for computing a danger-of-collision distance to the object, an alarm (46c, 48c, 54) ectuated by the computer (4) when the sensed distance of the object is equal to or less than the danger-of-collision distance compared by the computer (4), and a breke light (24) actuated upon the actuation of said alarm (46c, 48c, 54). The system also includes a control panel (6) having parameter presetting means for presetting preselected parameters concerning the vehicle (2), the vehicle driver, and the environment, which ere utilized by the computer (4) for computing the danger-of-collision distance to the object.



Data supplied from the esp@cenet database - Worldwide